

www.globlatekconveyors.com

## GLOBALTEK BOTTOMLESS SIDE BELT TRANSFER CONVEYOR

WITH TILTING CAPABILITIES AND ENCLOSED FRAME

The GLOBALTEK Bottomless Conveyor has variable speeds and is used in moving containers a short distance from one working/transportation conveyor to another. Designed to access the bottom side of the container for coding expiration dates, lot numbers, etc. The Gripper Belts are independently adjustable using an easy adjust handle wheel, accommodating containers up to 8" in diameter.



@globaltekconveyors

### TECHNICAL DATA

- BODINE AC MOTORS, 1/6 HP, 94 RPM, 39 LB/IN
- 115 VOLTS / 1 PH / 60 HZ
- ADJUSTABLE BELT OPENING: 0" TO 8"
- BELT SIZE: 36" L X 1" H
- FLOOR TO BELT HEIGHT: 35 1/2" TO 42"
- OVERALL MACHINE DIMENSIONS: 38" L X 24 1/2" W X 44" H

### OPTIONAL FEATURES

- PRINT HEAD BRACKET
- BOTTLE SLIDING PLATE
- LOCKING CASTERS

### WARRANTY

- 12 MONTHS (LIMITED WARRANTY)

www.globlatekconveyors.com



PINCH POINT PROTECTION



ALUMINIUM CRANK HANDLE



SPEED CONTROL



LABELING PADS AND BASES



TIMING BELT



MOTOR



TIMING & IDLER PULLEY

## GLOBALTEK BOTTOMLESS SIDE BELT TRANSFER CONVEYOR

WITH TILTING CAPABILITIES AND ENCLOSED FRAME