

BUNDLING TUNNELS PROFESSIONAL SERIES

MODELS

ETB2416, ETB2420, ETB3616, ETB3620, ETB4816, ETB4820, ETB5616, ETB5620, ETB7016, ETB7020

BUILT RIGHT...PRICED RIGHT

Proven reliable over and over again, EASTEY bundling tunnels provide you with all the quality features found in much higher priced machines. They are designed and built to give you all the features needed for positive shrinking of polyethylene film.

RUGGED DESIGN

EASTEY'S top of the line bundling tunnels are expertly welded on 12 gauge steel frames and designed to handle the day to day abuse of most bundling applications. Each tunnel utilizes four-directional variable air flow to provide a positive shrink. See for yourself why EASTEY has been a leader in the shrink packaging industry for over 25 years.

RELIABLE SHRINK PERFORMANCE

EASTEY'S ETB Series bundling tunnels offer the reliability needed to provide positive shrinking and are designed specifically for bundling applications.

STANDARD FEATURES

- Designed to shrink polyethylene film.
- All-welded main frame from 12 gauge steel
- 78" chamber length to ensure proper shrinking of film
- High temperature belting resists wear
- Sealed bearings (not bushings) on drive and idler shafts
- Adjustable digital solid state temperature control for a variety of films
- Four-directional air flow provides positive shrinking
- Variable air flow for a variety of products and applications
- Large ducting creates more air volume inside tunnel
- Airflow extended to the end of the chamber sides
- 4' product cooling conveyor on exit end
- Exit cooling fans accelerate shrinking
- Delayed cool down and over temperature protection
- Fold down electrical control panel for easy maintenance
- Heavy duty casters for transportation within plant
- Leveling legs provide sturdy base once in place
- Custom two part epoxy finish resists scratching
- Available in 220v single or 3-phase
- Easy to use design requires minimal training, maintenance, and trouble free operation
- Made in the USA















1. Reliable Shrink Perfomance

Proven Eastey tunnels provide positive shrinking of polyolefin, polyethylene and PVC films

2. High Temperature Belting

High temperature belting resists wear and is designed specifically for polyethylene films

3. Control Panel

Easy to use control panel lets users adjust for their specific application

4. Variable Air Flow

Four directional air flow provides positive shrinking for a variety of products and applications

MODEL Number		MACHINE DIMENSIONS WIDTH (A) HEIGHT (B) LENGTH (C)			CHAMBER DIMENSIONS WIDTH HEIGHT LENGTH			STANDARD POWER VOLTS AMPS PHASE			WEIGHT	SHP WT.
ETB2416	43"	56"- 72"	149"	24"	16" - 20"	78"	147"	480	30	3	1900 lbs	2000 lbs
	109 cm	142-182 cm	378 cm	60 cm	20 cm	76 cm	373 cm				861 kg	908 kg
ETB2420	43"	56"- 72"	149"	24"	16" - 20"	78"	147"	480	30	3	1900 lbs	2000 lbs
	109 cm	142-182 cm	378 cm	60 cm	40 - 50 cm	198 cm	373 cm				861 kg	908 kg
ETB3616	55"	56"- 72"	149"	36"	16" - 20"	78"	147"	480	60	3	2200 lbs	2300 lbs
	139 cm	142-182 cm	378 cm	91 cm	40 - 50 cm	198 cm	373 cm				997 kg	1043 kg
ETB3620	55"	56"- 72"	149"	36"	16" - 20"	78"	147"	480	60	3	2200 lbs	2300 lbs
	139 cm	142-182 cm	378 cm	91 cm	40 - 50 cm	198 cm	373 cm				997 kg	1043 kg
ETB4816	67"	56"- 72"	149"	48"	16" - 20"	78"	147"	480	100-120	3	2600 lbs	2700 lbs
	170 cm	142-182 cm	378 cm	121 cm	40 - 50 cm	198 cm	373 cm				1179 kg	1224 kg
ETB4820	67"	56"- 72"	149"	48"	16" - 20"	78"	147"	480	100-120	3	2600 lbs	2700 lbs
	170 cm	142-182 cm	378 cm	121 cm	40 - 50 cm	198 cm	373 cm				1179 kg	1224 kg
ETB5616	75"	56"- 72"	149"	56"	16" - 20"	78"	147"	480	100-120	3	2900 lbs	3000 lbs
	190 cm	142-182 cm	378 cm	142 cm	40 - 50 cm	198 cm	373 cm				1315 kg	1360 kg
ETB5620	75"	56"- 72"	149"	56"	16" - 20"	78"	147"	480	100-120	3	2900 lbs	3000 lbs
	190 cm	142-182 cm	125 cm	142 cm	40 - 50 cm	198 cm	373 cm				1315 kg	1360 kg
ETB7016	89"	56"- 72"	149"	70"	16" - 20"	78"	147"	480	100-120	3	3200 lbs	3300 lbs
	226 cm	142-182 cm	155 cm	177 cm	40 - 50 cm	198 cm	373 cm				1451 kg	1496 kg
ETB7020	89"	56"- 72"	149"	70"	16" - 20"	78"	147"	480	100-120	3	3200 lbs	3300 lbs
	226 cm	142-182 cm	124 cm	177 cm	40 - 50 cm	198 cm	373 cm			3	1451 kg	1496 kg



