

**COMBO UNIT
PROFESSIONAL SERIES**

 **First in Quality. Built to Last.**



COMBO UNIT

PROFESSIONAL SERIES

MODELS

EC2016T(K), EC2028T(K)

A PERFECT MATCH

The Professional Series Combo Unit combines a rugged EASTEY L-sealer and shrink tunnel on a common frame with one power source. This allows for quick setup, perfect alignment and consistent product sealing. A common base with casters makes this a very portable system for transportation within the plant.

BUILT RIGHT...PRICED RIGHT

Proven reliable over and over again, these top of the line EASTEY L-Sealer Combo Units provide you with all the quality features found in much higher priced machines. They are designed and built to give you all the performance features needed for positive sealing a wide variety of films including polyolefin and PVC.

RUGGED DESIGN

EASTEY Professional Series Combo Units are expertly welded on 12 gauge steel frames and designed to handle the day to day abuse of manual sealing in most shrink wrap applications. Rugged seal arms and magnet clamping are just some of the features that provide the durability you have come to rely on from EASTEY. See for yourself why EASTEY has been a leader in the shrink packaging industry for over 25 years.

RELIABLE SEMI-AUTOMATIC L-SEALING

Easteey's Professional Series Combo Unit offers a L-sealer and shrink tunnel on a common frame for simple setup, perfect alignment and mobility within the plant.

STANDARD FEATURES


- Designed to seal most polyolefin, polyethylene, and PVC shrink films
- All-welded main frame from 1/4" cold rolled steel
- Live roller or stainless steel mesh belt conveyors
- Sealed bearings (not bushings) on drive and idler shafts
- Adjustable digital solid state temperature control for a variety of films
- Four-directional air flow provides positive shrinking
- Variable air flow and air velocity for a variety of products and applications
- Seal head casting equipped with head return cylinder
- Stainless steel film clamps hold film in place while sealing
- Available with hot wire or hot knife seal systems
- Hot knife seal systems available with mushroom (standard), pancake, arrow, or poly inserts
- Dual locking magnet clamps apply even pressure across sealbar
- Takeaway conveyor can be raised or lowered to center-seal product
- Automatic takeaway conveyor
- Heavy duty film cradle allows for easy changeovers and adjustments
- Adjustable pin perforator provides air evacuation
- Custom two-part epoxy finish resists scratching
- Heavy duty casters for transportation within plant
- Easy to use design requires minimal training and maintenance
- Made in the USA


First in Quality. Built to Last.


Automated Marking, Labeling & Packaging Systems

8785 Ag Park Drive North
Batavia, NY 14020
Tel: 585-344-4102 | Fax: 585-344-4109
www.marktecprods.com



1. **Takeaway Conveyor**
Seal head can be raised or lowered to center the seal on your product
2. **Pin Perf**
Adjustable pin perforator provides air evacuation in film which allows for proper film shrinkage
3. **Control Panel**
Easy to use control panel lets users adjust temperature settings for their specific application
4. **Tunnel**
Consistent air flow provides positive shrinking of polyolefin or PVC shrink films

MODEL NUMBER	MACHINE DIMENSIONS			CHAMBER DIMENSIONS			CONVEYOR	STANDARD POWER			WEIGHT	SHP WT.
	WIDTH	HEIGHT	LENGTH	WIDTH	HEIGHT	LENGTH	WIDTH	VOLTS	AMPS	PHASE		
EC2016T(K)	36"	64"	114"	16"	10"	36"	16"	220	60/50	1	1050 lbs	1150 lbs
	91 cm	163 cm	290 cm	41 cm	25 cm	91 cm	41 cm				476 kg	522 kg
EC2028T(K)	36"	64"	135"	16"	10"	36"	16"	220	60/50	1	1100 lbs	1200 lbs
	91 cm	163 cm	343 cm	41 cm	25 cm	91 cm	41 cm				499 kg	544 kg



7041 Boone Avenue North, Brooklyn Park, MN 55428
 (763) 428-4846 1 (800) 835-9344
 www.eastey.com info@eastey.com

