



**UCAT-3-STANDARD**

## UCAT-3-STANDARD • UCAT-3-W10

UCAT-3 Powered Unwinders provide a convenient way to manage your supply roll of labels and also eliminate stress on your printer by feeding labels to the printer. These Powered Unwinders also allow you to use larger supply rolls thereby minimizing your per unit label cost. Additionally, the supply roll doesn't have to be refreshed as often thus saving time and adding convenience.

Technical Specifications	UCAT-3-STANDARD	UCAT-3-W10
Max Roll Diameter (in)	12 (305-mm)	
Core Diameter (in)	3 (76-mm)	
Max Media Width (in)	6 (152-mm)	10 (254-mm)
Max Roll Weight (lbs)	17 (432-mm)	
Dimensions-HWD (in)	14 x 17 x 17 (356 x 432 x 432-mm)	14 x 17 x 19 (356 x 432 x 482-mm)
Weight (lbs)	26 (11.8-kg)	28 (12.7-kg)
Max Speed (ips)	120 (3048-mm)	
Min Speed (ips)	1 (25-mm)	
Max Torque (in-oz) <sup>1,2</sup>	183	
Max RPM <sup>1</sup>	388	
Number of Flanges	1	
Power Specifications <sup>1</sup>	120 - 220VAC in, 12VAC 40W Out	
Warranty	5 year limited warranty on Unwinder - 1 year limited warranty on Power Adaptor	
Available Options	<ul style="list-style-type: none"> <li>• FLANGE, CAT, OUT (Optional Outer Guide Flange)</li> <li>• HTO-CAT (High-Torque Option)</li> <li>• LTO-CAT (Low-Torque Option)</li> <li>• FOOTSWITCH</li> </ul>	

1. HTO-CAT increases Max Torque to 228 in-oz, Max RPM to 485, 304 ips (7,721-mm), and Power Out to 19VDC 80W. 09.2016.

2. LTO-CAT decreases Torque Range to 172 - 35 in-oz.