

# FlexPackPRO<sup>®</sup>

## XT SERIES TTO



### RUGGED

- Built with 7000 series aircraft-grade treated aluminum alloy and stainless steel.
- Vertically-integrated parts manufacturing to ensure quality control and precision assembly.
- Heavy-duty installation brackets and rollers crafted in-house to customer specifications.
- Robust long-life mechanical design requiring zero preventative maintenance.

### RELIABLE

- Clutchless ribbon drive and tension control design maximize uptime and long-term performance.
- Superior Festo<sup>®</sup> pneumatics assure image quality control & longer printhead life.
- Precision printhead assembly requires lower air pressure to achieve highest print quality.
- 300dpi Kyocera<sup>®</sup> printheads on self-leveling mounts provide superior code quality through every run.



*EXTRA LARGE RIBBON CAPACITY, HOLDS UP TO 3,280' ROLL.*



### VALUE

- Stainless steel 7" touchscreen controllers come standard with all models.
- ProCode<sup>™</sup> Professional coding design software comes free with all systems.
- Reasonably-priced ribbons, parts and service provide the industry's lowest total cost of ownership.
- On average, complete FlexPackPRO systems list for 25-40% lower than competitive TTO systems of comparable quality.

# FlexPackPRO<sup>®</sup>

Thermal Transfer Overprinting

# XT SERIES

Models:	130iXT / 130cXT	210iXT / 210cXT / 210cXTL	420iXT / 420cXT / 420cXTL
Printer Mode:	Intermittent / Continuous	Intermittent / Continuous / Continuous	Intermittent / Continuous / Continuous
Maximum Print Area (Width x Length):	32 mm x 76 mm / 125 mm (1.3" x 3" / 5")	53 mm x 76 mm / 125 mm / 250 mm (2.1" x 3" / 5" / 10")	107 mm x 76 mm / 125 mm / 250 mm (4.2" x 3" / 5" / 10")
Print Resolution:	300 dpi	300 dpi	300 dpi
Max Print Speed:	400 mm/s / 600mm/s (15.7 in/s / 23.6 in/s)	450 mm/s / 800mm/s / 800mm (17.7 in/s / 31.5 in/s / 31.5 in/s)	400 mm/s / 600mm/s (15.8 in/s / 23.6 in/s)
Print Gap:	0.5 mm (0.02")	0.5 mm (0.02")	0.5 mm (0.02")
Standard Ribbon Width:	35mm (1.4")	55mm (2.2")	110mm (4.3")
Maximum Ribbon Length:	1,000 m (3,280')	1,000 m (3,280')	1,000 m (3,280')
Ribbon Saver Features:	Yes	Yes	Yes
Ribbon Loading:	Integrated Cassette	Integrated Cassette	Integrated Cassette
Standard User Interface:	7" Color Touchscreen (stainless)	7" Color Touchscreen (stainless)	7" Color Touchscreen (stainless)
Software:	ProCode™ Professional	ProCode™ Professional	ProCode™ Professional
Barcodes:	All	All	All
Standard Communication:	USB, Ethernet, RS232	USB, Ethernet, RS232	USB, Ethernet, RS232
Printer Dimensions (Height x Width x Depth):	180 mm x 265 mm x 240 mm (7.09" x 10.43" x 9.45")	180 mm x 265 mm x 250 mm (7.09" x 10.43" x 9.84")	180 mm x 265 mm x 305 mm (7.09" x 10.43" x 12.01")
Printer Weight:	10 kg (22 lbs)	11 kg (24 lbs)	13 kg (27 lbs)
Power Supply:	110 - 120 / 200 - 240 VAC, 50 / 60 Hz	110 - 120 / 200 - 240 VAC, 50 / 60 Hz	110 - 120 / 200 - 240 VAC, 50 / 60 Hz
Air Supply:	3 bar / 44 psi (max)	3 bar / 44 psi (max)	3 bar / 44 psi (max)
Operating Temperature:	5° - 50° C (41° - 122° F)	5° - 50° C (41° - 122° F)	5° - 50° C (41° - 122° F)

## FlexPackPRO<sup>®</sup>

Thermal Transfer Overprinting

CORPORATE LOCATIONS  
 GEORGIA | ILLINOIS | NEW JERSEY

(800) 758-9219  
[gopro@flexpackpro.com](mailto:gopro@flexpackpro.com)  
[www.flexpackpro.com](http://www.flexpackpro.com)



8785 Ag Park Drive North  
 Batavia, NY 14020  
 Tel: 1-800-627-5832 | Fax: 585-344-4109

[www.marktecprods.com](http://www.marktecprods.com)

