

### CAT-3 • CAT-3-R16 • CAT-3-R18

The CAT-3-CHUCK Rewinder Series affords the fastest loading and unloading of cores and label rolls, and is ideal for high-volume production environments, label slitting applications, or anywhere the ultimate convenience in Rewinders is desired.



**CAT-3-CHUCK-220**

| Technical Specifications                 | CAT-3   | CAT-3-R16   | CAT-3-R18   |
|--|---|---|---|
| <b>Max Roll Diameter (in)</b>            | 12 (305-mm)   | 16 (406-mm)   | 18 (457-mm)   |
| <b>Core Diameter (in)</b>                | 3 (76-mm)   |   |   |
| <b>Max Media Width (in) <sup>1</sup></b> | 6 - 10 (152 - 254-mm)   |   |   |
| <b>Max Roll Weight (lbs)</b>             | 20 (9-kg)   | 32 (14.5-kg)  | 50 (22-kg)  |
| <b>Dimensions-HWD (in)</b>               | 14x12x17 (355 x 305 x 432-mm)   | 19x16x17 (482 x 406 x 432-mm)   | 20x18x19 (508 x 457 x 482-mm)   |
| <b>Weight (lbs) <sup>1</sup></b>         | 28 - 30 (12.7 - 13.6-kg)  | 30 - 32 (13.6-kg - 14.5-kg)   | 34 - 36 (15.4 - 16.3-kg)  |
| <b>Max Speed (ips)</b>                   | 240 (6096-mm)   | 320 (8128-mm)   | 360 (9144-mm)   |
| <b>Min Speed (ips)</b>                   | 0.5 (13-mm)   |   |   |
| <b>Max Torque (in-oz) <sup>2,3</sup></b> | 183   | 228   | 228   |
| <b>Max RPM <sup>2</sup></b>              | 388   | 485   |   |
| <b>Number of Flanges</b>                 | 2   |   |   |
| <b>Power Specifications</b>              | 120 - 220VAC in, 12VAC 40W Out <sup>1</sup>   |   | 120 - 220VAC in, 19VDC 80W Out  |
| <b>Warranty</b>                          | 5 year limited warranty on Rewinder - 1 year limited warranty on Power Adaptor  |   |   |
| <b>Available Options</b>                 | <ul style="list-style-type: none"> <li>• HTO-CAT (Hi-Torque Option)</li> <li>• LTO-CAT (Lw-Torque Option)</li> <li>• ADAPT-326 (6" Core Adaptor)</li> <li>• FOOTSWITCH</li> </ul> | <ul style="list-style-type: none"> <li>• LTO-CAT (Lw-Torque Option)</li> <li>• ADAPT-326 (6" Core Adaptor)</li> <li>• FOOTSWITCH</li> </ul> | <ul style="list-style-type: none"> <li>• LTO-CAT (Lw-Torque Option)</li> <li>• ADAPT-326 (6" Core Adaptor)</li> <li>• FOOTSWITCH</li> </ul> |

1. Depends on whether you order the CHUCK, CHUCK-220, or CHUCK-10 model

2. **HTO-CAT** increases Max Torque to 228 in-oz, Max RPM to 485, 304 ips (7,721-mm), and Power Out to 19VDC 80W.

3. **LTO-CAT** decreases Torque Range to 172 - 35 in-oz.