

Limitag V5 CMYK UV LED

Full color printing

Online decoration
and coding



ADVANTAGES

- Real-time box personalization
- Stock reduction of pre-printed boxes
- Flexibility in short runs and promotions
- Practically zero maintenance
- No interruptions when adding consumables
- Coding and decoration with just one system



CHARACTERISTICS

- Native 180dpi resolution
- Multiple densities and contrasts
- High quality barcodes. GS-1 Standard
- Intuitive user environment
- On screen preview of printing layout (WYSIWYG)
- Oil based and UV LED ink
- Integrated Web Server
- External message selection through hardware
- Integrated post-print barcode scanner
- Scripting for totalwork personalisation
- Multiple integrated colour profiles



Graphic Solid Inks, Inc.
6845 Shiloh Rd E
Alpharetta, GA 30005
Ph: 678.264.4008
Email: info@gsinks.com
gsinks.com

SPECIFICATIONS

PRINT

Printer head resolution: 180 dpi

Print speed:
30 m/min @ 180dpi
0.2 - 96 m/min according to the resolution

Height: 72 mm

Maximum length: 1100 mm

Densities: 3 levels

Fonts: True Type™, Open Type™ fonts

Character coding: Unicode

Barcodes: GS-1 Standard
EAN/UPC, ITF-14, GS1-128, GS1 Datamatrix, GS1 QR Code

Printing of variable fields:
User (personalised fields) and automatic fields (expiration dates, shift codes, counters)

Orientation:
Vertical (side of product)
Horizontal (product cover)

Encoder:
Automatic speed calibration

ELECTRICAL

Power supply:
Switch selectable
88-132 VAC | 176-264 VAC
47-63 Hz, 156 W (max)

Input:
2 x printer signals
1 x encoder
5 x programmable electronics (external message selection)

Output (through colour):
2 x programmable electronics
2 x status indicators

Communication ports:
1 x RS-232
1 x RS-422 / 485 / 232 (optional)
2 x Ethernet 10/100
2 x USB
1 x Wi-Fi (Optional)

ENVIRONMENTS

Working environment:
5 - 45 °C (41 - 113°F)

Protection:
IP 50 (controller)

USER INTERFACE

15" colour touch screen
Message selection with preview WYSIWYG
Diagnostics
Integrated message editor

COMMUNICATIONS

Individual communications protocol
Webserver
Windows™ Driver
Connectivity with external database and ERP
Remote assistance

OTHERS

Weight:
20kg (controller)
10kg (head)

Ink:
UV LED ink

Colors:
Black (high contrast)
Cyan
Magenta
Yellow



PRINTABLE PRODUCTS

Cardboard, glossy paper, art paper, paper, fabrics, wood, plastic, metal, nylon, EPS, and more

OPTIONS

Post-print barcode verification, alarm beacon, barcode scanner for selection of products

Limitag v5 CMYK UV LED

UV LED

UV LED




Printing immediately sets
Useful, long life span with low maintenance
Energy efficient

FEATURES

Several heights available
Instant on/off
Safety through double activation input
Adjustable intensity

DIMENSIONS



Graphic Solid Inks, Inc.
6845 Shiloh Rd E
Alpharetta, GA 30005
Ph: 678.264.4008
Email: info@gsinks.com
gsinks.com